The world of RTS controls







WALL-MOUNTED CONTROL UNITS

Interior control units **Smoove 1 Origin RTS**

Wireless control unit, 1 channel.

> Raise, lower, stop and "my" favourite functions.

Exterior control unit

Metal keypad RTS Secure, wireless metal panel.

- > Controls 2 motorised devices
- > Access control with master code and 4 personal codes.
- > Intruder protection (up to 6 digits per code).
- > Piracy prevention.
- > Back-lit keys.

SOMFY RECOMMENDS -

Consider equipping your store with **RTS lighting receivers**. Take advantage of the comfort of controlling your lighting remotely.

Indoor lighting receivers RTS







REMOTE CONTROL

Keytis 4 RTS

Pocket remote control.

> Controls 4 motorized RTS devices.

Keygo RTS

Pocket remote control.

- > Controls 4 motorized RTS devices.
- > Impact and moisture-resistant.

Keytis 2 RTS

Pocket remote control.

> Controls 2 motorized RTS devices.


THE SOMFY +

centralization

Make it easier to control your everyday environment, operating all your metallic shutter, awning and interior blinds with the shop closure control. One click on the remote control operates all the shop's RTS equipment: closure, sun protections, lighting, etc., without forgetting anything.



- 4 channel remote control + 1 for centralization.
- > Up, down, stop et "my" favorite position functions.



Centreo range

Motorized closures for commercial access

Quality makes all the difference from the start







0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0 0 0 0 0 0 0 0 0 0000000000 000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000 0000000000

00000000000

Centreo range

Now available in a radio version

Already hugely popular in the wired version, the range of Somfy Central motors is now offering all the benefits of secure radio technology: a high-performance installation, unrestricted by wiring, and much easier to use, with a wide selection of wireless commands. Using the Centreo radio range, you have a high-added value product to boost sales.

Greater ease of integration

> Integration on the tube is simplified and without **constraint.** Choice of motor direction when installing it on the tube and when adjusting the end-limits.

Optimised installation

- > Wireless installation: clean working area, no drilling or channels dug in the walls to connect the motor to controls or to a key unit. Only the motor needs mains
- > Radio antenna built into the motor drive: no external receiver to install.
- > Adjustment of the end-limits made easier: accurate memorisation of the position of the curtain by the
- > Adjustments without removing the shutter box **or touching to the motor.** Faster and more accurate re-adjustment of the motor rotation and end limits since a remote control.
- **> Add a command:** easily done by the user. No need to travel, one call does it!

A COMPLETE OFFER





Situo RTS Wall mounted remote control

> Up, down, stop, and "my" favourite position functions.

Centralization means time savings for the user

> Thanks to the compatibility of Somfy systems, you have the possibility of easily centralising the metal curtain, sunscreens, and one light from a single transmitter.

Closing to the intermediary position "my"

> Signal pre-closing of the store by lowering the curtains to the intermediate position of your choice with one "click".



Range of 200m in an open space, or 20m through two reinforced concrete walls.


No wiring Between the motor, the switch, and the receiver. Easy to set and program.

Compatible with all of Somfy's range of automatic

Technology developed by Somfy, world leader in automatic control for buildings.

Centreo range

Quality of a closure, an everyday requirement



A compact motor, with a wide range of products


Its compact size means that Centreo can provide motor drive for narrow curtains. The range offered by Centreo, whether wired or radio-controlled, means you can find the right motor, whatever the size of the closure.

Centreo	Torque Nm	For curtains up to	Power W	Current A	Speed rpm	Wheel Ø	Tube Ø	End-of-travel capacity	Brake and declutching	Weight kg		gth m Lb
Centreo 1	75	150 kg ⁽¹⁾	345	1.5	10	200 - 220	60 (2)	12 Tr	With & without	6.5 (3)	342	-
Centreo 2	100	200 kg ⁽¹⁾	390	1.7	10	200 - 220 - 240	60 ⁽²⁾ - 76	12 Tr	With & without	6.8 (3)	357	342
Centreo 3	140	255 kg ⁽¹⁾	500	2.2	10	220 - 240	60 - 76	12 тг	With & without	7 (3)	372	357
Centreo 4	200	350 kg ⁽¹⁾	800	3.5	10	220 - 240	60 - 76	12 Tr	With	10.5 ⁽³⁾	342	342

	Centreo RTS	Torque Nm	For curtains up to	Power W	Current A	Speed rpm	Wheel Ø	Tube Ø	End-of-travel capacity	Brake and declutching	Weight kg		igth ^{im} Lb
ı	Centreo 1	75	150 kg ⁽¹⁾	345	1.5	10	200 - 220	60 ⁽²⁾	20 Tr	With	6.5 ⁽³⁾	372	357
	Centreo 2	100	200 kg ⁽¹⁾	390	1.7	10	200 - 220 - 240	60 ⁽²⁾ - 76	20 тг	With	6.8 (3)	372	357
	Centreo 3	140	255 kg ⁽¹⁾	500	2.2	10	220 - 240	60 - 76	20 Tr	With	7 (3)	372	357

⁽¹⁾ for a perfectly-balanced curtain, with a wheel Ø of 220 mm.





Efficient declutching

Tried and tested reliability

Long-life performance


100% safe

Easy to install for any technology









 $^{^{(2)}}$ motor can be adapted for tube \emptyset of 34, 42 and 48 mm, using an adaptor kit.

⁽³⁾ weight of motor with a wheel Ø of 220 mm.